

ULTRAGuard™

WerkMaster

1448 Charlotte Road, North Vancouver, BC, Canada V7J 1H2
tel: 604.629.8700 | fax: 604.990.9538 | www.werkmaster.com

SECTION 1 - PRODUCT IDENTIFICATION

Trade Name: UltraGuard

Date: June 9, 2010

Manufacturer Code ID: Concrete Sealer

WerkMaster certifies that its products comply with all provisions of the Toxic Substances Control Act (TSCA), unless otherwise stated by ingredient in Section 2.

The percent by weight composition data given in sections 2 and 10 are NOT SPECIFICATIONS, but are based on 'target' formula values for each ingredient in the product. The data are presented as ranges for low hazard ingredients and single point values for ingredients of regulatory concern. Actual batch concentrations will vary within limits consistent with separately established product specifications.

SECTION 2 – INGREDIENTS

This product contains no reported carcinogens or suspected carcinogens. This product contains no reportable hazardous ingredients. This Material Safety Data Sheet contains information on good industrial practice for safe handling of all industrial chemicals.

SECTION 3 – PHYSICAL DATA

Boiling Range: High–N/A Low–212°F

Vapour Pressure: See Section 2

Odour: Moderate

Odour Threshold: N/A

Theoretical VOC, Calculated: 0.693 lb/gal
(If applicable see Section 10 for further VOC information.)

Water Solubility: Completely Dispersable

Freezing Point: N/A

Appearance: White, Milky

Physical State: Liquid

pH: N/A

Theoretical Weight per Gallon, Calculated: 8.9898 lb/gal

Theoretical Specific Gravity, Calculated: 1.08

Distribution: N/A

Mechanical Impact Explosion: No known hazard

Static Electricity Explosion: No known hazard

SECTION 4 – FIRE AND EXPLOSION HAZARD INFORMATION

Lowest Closed Cup Flash Point: 248°F

Extinguishing Media: None Required

Explosion Hazards: None known

OSHA Flammability Classification: N/A

DOT Flammability Classification: N/A

Lower Flammable limit in Air: Lower–N/A % by volume.

DOT Shipping Name: Plastic Materials, Liquid

Special Fire Fighting Procedures: None known

Freight Classification: NMFC: 149980/SUB 2. LTL Class 55 Resin Compounds, Liquid.

SECTION 5 – HEALTH HAZARD INFORMATION


HMIS Hazard Class:

Health = 1

Flammability = 0

Reactivity = 0

Other = NA



Rankings:

0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme

Eye Contact: Direct contact with product may cause irritation.

Skin Contact: Prolonged or repeated contact with product may cause mild irritation.

Inhalation: Prolonged overexposure to vapours or dust in poorly ventilated areas may cause nose and throat irritation.

Ingestion: May cause mouth, throat, esophagus and stomach irritation, nausea, vomiting and diarrhea.

Emergency and First Aid Procedures: In cases of eye contact, flush immediately with plenty of water for at least 15 minutes and seek medical attention; for skin, wash thoroughly with soap and water while removing contaminated clothing and shoes. Wash contaminated clothing. Thoroughly clean contaminated shoes. If affected by inhalation of vapours or spray mist, remove to fresh air. If swallowed, seek medical attention immediately.

California Proposition 65 Information: This material contains no intentionally-added ingredients, covered by the California 'Safe Drinking Water and Toxic Enforcement Act of 1986' (Proposition 65), unless specifically stated under OTHER HEALTH HAZARDS, by individual chemical.

SECTION 6 – REACTIVITY INFORMATION

Stability: Stable

Hazardous Polymerization: None under normal conditions

Conditions to Avoid: Protect from freezing. Do not store at or below 32°F. Protect from elevated temperatures.

Incompatibility (Materials to Avoid): None reasonably foreseeable.

Hazardous Decomposition Products: Incomplete combustion can produce carbon monoxide.

SECTION 7 – SPILL, LEAK AND DISPOSAL PROCEDURES

Spills/leaks: Avoid breathing vapours. Ventilate area. Contain and remove with inert absorbent and non-sparking tools.

Disposal: Dispose of in accordance with federal, state, and local regulations. Do not incinerate closed containers. Incinerate in approved facility.

SECTION 8 – SPECIAL PROTECTIVE EQUIPMENT

Eye and Facial: Avoid contact with eyes. Use safety eye-wear with splash guards or side shields.

Respiratory: Avoid breathing any spray or mist. If spraying, wear mechanical filter respirator to remove solid particles of over-spray. Follow respirator manufacturer's directions for respirator use.

Ventilation: Provide general clean air dilution or local exhaust ventilation in volume and pattern to prevent air contaminant concentration build up. Refer to OSHA standard 1910.94.

Protective Gloves: If there is potential for prolonged or repeated skin contact, wear plastic gloves for the duration of anticipated exposure.

Other Protective Equipment: None normally required. If unable to avoid prolonged or repeated contact with skin, wear protective clothing.

SECTION 9 – SPECIAL PRECAUTIONS

Storage: Do not store above 100°F.

Handling: Keep containers closed when not in use and upright to prevent leakage.

Other: Do not take internally. Wash hands after using and before eating. Keep out of reach of children. For industrial use only.

SECTION 10 – SARA TITLE III INFORMATION

SARA 313 Information: This product contains NONE of the substances subject to the reporting requirement of Section 313 of Title III of the Superfund Amendments and Reauthorization Act 1986 and 40 CFE Part 372.

SECTION 11 – OTHER INFORMATION

The information contained herein is based on data considered to be accurate. While the information is believed to be reliable, no warranty is expressed, or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Since the use of this information and the conditions and use of this product are controlled by the user, it is the user's obligation to determine the conditions of safe use of the product.