

# ULTRaseal™

## DESCRIPTION

Penetrating fluouopolymer sealer for concrete.

## INTENDED USE

- Sealer for all concrete where no colour change and no gloss is desired.

## PRODUCT FEATURES

- Excellent resistance to oil and water based staining agents
- No colour change
- Provides anti-slip properties
- Can be applied at low temperatures (40°F or higher).

## PHYSICAL PROPERTIES

- Flash Point ..... >250°F
- Viscosity ..... Liquid
- Colour ..... Clear
- Type of Solids ..... Info not available
- Boiling Point ..... 212°F
- Odour ..... Mild
- pH ..... 7.8

## LIMITATIONS OF USE

For industrial/professional use only.

## ORDERING INFORMATION

Call WerkMaster toll free:  
1.866.373.WERK

## WerkMaster Chemicals Inc.

1448 Charlotte Road, North Vancouver, BC, Canada V7J 1H2  
tel: 604.629.8700 | fax: 604.990.9538 | [www.werkmaster.com](http://www.werkmaster.com)

## SURFACE PREPARATION

Concrete must be fully cured and be clean, dry and free from all other sealers, dirt, oil and any other substance that will prevent penetration or curing of product.

## MIXING INSTRUCTIONS

No mixing required.

## APPLICATION INSTRUCTIONS

Apply using sprayer, brush, roller or microfiber pad saturating area and keeping wet for 5-10 minutes. Remove excess before product has dried.

## STORAGE

DO NOT freeze. Store in a cool, dry, well-ventilated place.

## COMPLIANCES

VOC Less than 100gm/L

## CHEMICAL RESISTANCE

Excellent repellence of water, oil and alcohol based stains. Resists chemical degradation, biological growth and efflorescence. Vapour permeable – reduces crackling, spalling and freeze /thaw damage.

## PRECAUTIONS

Please refer to the appropriate material safety data sheet (MSDS) prior to using this product.

For technical assistance, please call 1-866-373-WERK

FOR INDUSTRIAL/PROFESSIONAL USE ONLY

Keep containers closed when not in use and upright to prevent leakage. DO NOT take internally. wash hands after using and before eating. Keep out of reach of children. Dispose of according to law and local regulations.

## WARRANTY

WerkMaster Chemicals Inc. will replace any material found to be defective. Because the storage, handling and application of this material is beyond our control, we can accept no liability for the results obtained.

## DISCLAIMER

All information on this data sheet is based on laboratory testing and is not intended for design purposes. WerkMaster Chemicals Inc. makes no representations or warranties of any kind concerning this data.

*Taking it to the Wall!*